

# FLOW SIDE G2

## PROJECT DETAILS

PROJECT

TYPE



NOTES

Bringing LED strip lighting to the next level, Flow is an advanced silicone strip that incorporates more flex and longevity than ever before. Flow Side is perfect for designs that require a horizontal bend, either left or right. With the ability to curve up to 300mm.

- Side emitting – For curving around surface, requiring indirect light.
- UV & chemical resistant.
- 5W, 10W, 15W options.
- High CRI – Bringing out the colours in the space.

IP 67 – Suitable for outdoor & wet applications.

- Front, side, and bottom cable entry connection options.



DIMENSIONS

W 16 mm

H 17 mm

### LUMINAIRE OPTIONS

LED & LUMENS OPTIONS (3000K | 4000K)

5W PER METER  
294lm | 294lm

10W PER METER  
537lm | 548lm

15W PER METER  
824lm | 824lm

### GENERAL SPECIFICATIONS

LED LUMENS 3000K | 4000K

5W p/m 294lm | 294lm

10W 537lm | 548lm

p/m 15W 824lm | 824lm

EFFICIENCY P/METER Up To 59 lm/w

COLOUR 3000K, Warm White  
4000K, Cool White  
Extruded Silicone

MATERIAL White

FINISH 120°

BEAM 90+

CRI 67

IP SDCM  $\leq 2$

COLOUR DEVIATION 300mm

BENDING DIAMETER > 54,000hrs L70B10

LIFETIME 5 Years

WARRANTY

### PRODUCT CODES

5W 3000K, 120° 10-FL1617S053

4000K, 120° 10-FL1617S054

10W 3000K, 120° 10-FL1617S103

4000K, 120° 10-FL1617S104

15W 3000K, 120° 10-FL1617S153

4000K, 120° 10-FL1617S154

### COMPATIBLE CASAMBI DEVICES

BasicDIM 24V Wireless 71-CAS24V 71-

4ch BasicDIM Driver 24V CAS24V150 71-

150W BasicDIM Driver CAS24V100 71-

24V 100W BasicDIM CAS24V60 71-

Driver 24V 60W BasicDIM CAS24V35

Driver 24V 35W



### CUTTING LENGTH & MAX RUN LENGTH

LED CUTTING LENGTHS MAX RUN LENGTH (Integrated | DIY)

5W 50mm 50mm 30m | 15m 20m |

10W 50mm 10m 15m | 6.6m

15W

Allow for 9mm extra on each side for end caps.

espo  
LIGHTING

espo.com.au

ABN 53 136 770 566

[joseph@espo.com.au](mailto:joseph@espo.com.au)

+618 8117 8633



## FLOW SIDE ACCESSORIES

### SIDE CABLE ENTRY

Side Cable, Right Entry	10-FL1617SPSRE
Side Cable, Left Entry	10-FL1617SPSLE
DIMENSIONS	N/A

CABLE ENTRY	Side
-------------	------

### REAR CABLE ENTRY

Rear Cable, Right Entry	10-FL1617SPRER
Rear Cable, Left Entry	10-FL1617SPREL
DIMENSIONS	N/A

CABLE ENTRY	Rear
-------------	------

### STRAIGHT CABLE ENTRY

Straight Cable, Right Entry	10-FL1617SPFER
Straight Cable, Left Entry	10-FL1617SPFEL
DIMENSIONS	N/A

CABLE ENTRY	Front
-------------	-------

### ALUMINIUM PROFILE

Aluminium Profile	10-FL1617P2
DIMENSIONS	1000 (L) x 20.2 (W) x 20.8 (H) mm
MATERIAL	Aluminium
FINISH	Silver

### MOUNTING CLIPS (SET OF 4)

Mounting Clips	10-FL1617MC
DIMENSIONS	20 (L) x 16.6 (W) x 12.4 (H) mm
MATERIAL	Aluminium
FINISH	Silver
NOTES	Each meter requires 4 clips and 4 screws

### END CAP

Mounting Clips	10-FL1617SEC
DIMENSIONS	26.5 (L) x 17 (W) 24.2 X (H) mm
MATERIAL	Stainless Steel
IP	67

espo  
LIGHTING

espo.com.au  
ABN 53 136 770 566

[joseph@espo.com.au](mailto:joseph@espo.com.au)  
+618 8117 8633

