




SILO 40 SURFACE MOUNTED



PROJECT DETAILS

PROJECT:

TYPE:


NOTES:

FEATURES

- + Minimalist cylinder design, available in various colours and lengths
- + Sophisticated lens technology for enhanced visual comfort
- + Black baffle for reduced glare
- + Seamless canopy with quick connection for easy installation
- + Compatible with remote Casambi CBU-TED Bluetooth Controllable Dimmer (71-CASCBU)



DIMENSIONS (mm)



GENERAL SPECIFICATIONS

LED	6W
Lumens	520 lm (3000K & 4000K)
Efficacy	79 lm/w (3000K & 4000K)
Colour Temp	<input type="checkbox"/> 3000K, Warm White <input type="checkbox"/> 4000K, Cool White
Material	Powder Coated Aluminium
Finish	White Black
Beam	15° 24° 36° 45° 60°
CRI	92+
IP	20
Colour Deviation	SDCM ≤2
UGR	<15
Lifetime	>55,000hrs L80 B10
Warranty	5 Years

Additional Lens Options	15° Lens	118-SIL4015
	25° Lens	118-SIL4024
	36° Lens	118-SIL4036
	45° Lens	118-SIL4045

Additional Baffle Options	Black Baffle	118-SIL40BB
	White Baffle	118-SIL40BG
	Gold Baffle	118-SIL40BG

DRIVER SPECIFICATIONS

Power	150mA 240V Built-In Flicker Free Dimmable Driver
Dimming	Phase-Cut Dimming
Power Factor	>0.90

Remote DALI dimming available upon request

PRODUCT CODE

280, White, 3000K, 60°	118-SIS42806W603
280, White, 4000K, 60°	118-SIS42806W604
280, Black, 3000K, 60°	118-SIS42806B603
280, Black, 4000K, 60°	118-SIS42806B604
380, White, 3000K, 60°	118-SIS43806W603
380, White, 4000K, 60°	118-SIS43806W604
380, Black, 3000K, 60°	118-SIS43806B603
380, Black, 4000K, 60°	118-SIS43806B604
580, White, 3000K, 60°	118-SIS45806W603
580, White, 4000K, 60°	118-SIS45806W604
580, Black, 3000K, 60°	118-SIS45806B603
580, Black, 4000K, 60°	118-SIS45806B604