EDGE MINI G3

Incorporating a minimal trim design, with advanced LED engines to achieve intense illumination with a high lumen per watt efficacy. Our Generation 3 Series of downlights are unmatched, featuring higher quality lighting, more effective heat dissipation, and stronger LEDs.

- Adjustable head up to 25°.
- Precision reflector with clear lens – for better light distribution.
- Specially designed heat sink – for class leading heat dissipation.
- Deep set lamp position – for visual comfort and glare reduction.
- Generation 3 LED technology – up to 15% more lumens.



DIMENSIONS	W Ø86 mm H 105 mm
CUT-OUT	I Ø76mm

LUMINAIRE OPTIONS

LED & LUMENS OPTIONS (3000K | 4000K)

10W	**8W**
1175lm | 1275lm	1025lm | 1125lm

BEAM OPTIONS (REFLECTOR / LENS)

60° REFLECTOR STANDARD | **60°** | **36°** | **24°** | **15°**

FINISHES

☐ **WHITE** ■ **BLACK**

GENERAL SPECIFICATIONS

EFFICACY	Up to 140 Lm/W
COLOUR	3000K, Warm White 4000K, Cool White
MATERIAL	Powder Coated Material
CRI	92+
IP	44
COLOUR DEVIATION	SDCM ≤2
UGR	<14
LIFETIME	> 55,000hrs L90B10
WARRANTY	7 Years

DRIVER SPECIFICATIONS

DIMENSIONS	L 98 x W 40 x H 22mm
POWER	300mA | 250mA 240V Remote Flicker Free Dimmable Driver
DIMMING	Phase Cut Dimming
POWER FACTOR	> 0.90

PROJECT DETAILS

PROJECT

TYPE

NOTES

PRODUCT CODES

White, 3000K, 60°	**118-ED3M11W603**
White, 4000K, 60°	**118-ED3M11W604**
Black, 3000K, 60°	**118-ED3M11B603**
Black, 4000K, 60°	**118-ED3M11B604**

ACCESSORIES

36° Reflector	**118-RFLP36**
24° Reflector	**118-RFLP24**
15° Reflector	**118-RFLP15**
60° Lens	**118-LSE360**
36° Lens	**118-LSE336**
24° Lens	**118-LSE324**
15° Lens	**118-LSE315**

DRIVER CODES

DRIVER SOLD SEPERATELY

10W	**118-300MA**
8W	**118-250MA**

DALI DIMMING AVAILABLE UPON REQUEST

Espo Lighting
espo.com.au
joseph@espo.com.au
+618 8117 8633